



INTERIOR  
EXTERIOR



# DEKS OLJE® D.2

## HIGH GLOSS OIL VARNISH

<b>Product description</b>	<p>DEKS OLJE® D.2 is a varnish like, tough, flexible and durable finish that enhances the natural beauty of the wood. Easy to maintain and apply the more coats of DEKS OLJE® D.2 applied the higher the gloss finish. Unlike traditional varnishes DEKS OLJE® D.2 will not craze or blister and because of DEKS OLJE® D.1*'s penetrating qualities will not peel or flake as water is unable to get in to the wood.</p>
<b>Properties</b>	<p>Flexible film that does not craze, peel or flake.          High gloss finish.          Highly transparent varnish – enhances the natural beauty of the wood.          Long term protection.          No sanding between coats.          Easy maintenance.          Easy repair, no stripping.</p>
<b>Basic uses</b>	<p>Hardwoods and Exotic hardwoods - Teak, Ipe, Mahogany, Iroko, Bangkirai...          New or weathered wood.          Exterior use - Rubbing Strakes, Handrails, Wheel houses, booms, masts...          Interior use - Furniture, Seating...          Horizontal &amp; Vertical.</p>
<b>Technical data</b>	<p><b>Finish:</b> Gloss.  <b>Vehicle Type:</b> Alkyd-Urethane Resins.  <b>Solvent Type:</b> Solvent.  <b>Viscosity:</b> Semi-Fluid.  <b>Specific Gravity:</b> 0,910 ± 0,05 (68°F - 20°C).  <b>Physical State:</b> Liquid.  <b>Solid Content:</b> 56 % ± 5.  <b>Flammability:</b> Not classified as flammable.  <b>Flash point:</b> &gt; 140°F (60°C).  <b>Shelf Life:</b> 2 years in original unopened packaging.  <b>Container Size:</b> 1L (1.06 U.S QUART), 2.5L (0.66 U.S. GALLON), 20L (5.28 U.S. GALLON).  <b>Color:</b> Amber.  <b>Dry time:</b> 12-24 hours, depending on temperature and humidity.  <b>Re-coating Time:</b> 12 hours.  <b>Setting up Time Before Use:</b> 3 days.  <b>VOC:</b> Does not exceed 399 g/l (3.32 lb/gal).</p>
<b>Application tools</b>	<p>Brush, Roller.</p>
<b>Good application practice</b>	<p>Cover everything you do not wish to paint.          Apply between 46°F (8°C) and 95°F (35°C).          Do not apply in direct sunlight or on to hot surfaces.</p>

The information set out cons are purely illustrative and are not the responsibility of the manufacturer, the application of products not made under his supervision.

<b>Surface preparation</b>	<p><b>New wood:</b></p> <ul style="list-style-type: none"> <li>All new wood must be treated with DEKS OLJE® D.1* as per label directions.</li> </ul> <p><b>Weathered wood previously treated with DEKS OLJE® D.1*:</b></p> <ul style="list-style-type: none"> <li>Surfaces must be clean, dry and free of all surface contamination.</li> <li>If DEKS OLJE® D.1* has lightened to a light gray finish, clean and restore as per label and technical data directions before applying DEKS OLJE® D.2.</li> </ul> <p><b>Wood already treated with DEKS OLJE® D.2:</b></p> <ul style="list-style-type: none"> <li>See maintenance.</li> </ul>
<b>Application</b>	<ul style="list-style-type: none"> <li>DO NOT THIN. USE AS IS.</li> <li>Apply 6 coats of DEKS OLJE® D.2 allowing a minimum of 12 hours between coats.</li> <li>All coats should be applied within 1 month.</li> <li>Sanding between coats is not required.</li> <li>For an extra high gloss finish, sand between the last 2 coats with 600 grit paper .</li> <li>Allow 3 days for DEKS OLJE® D.2 to set-up and dry, before putting the boat in service.</li> </ul>
<b>Coverage</b>	161 ft <sup>2</sup> (15 m <sup>2</sup> ) per liter.
<b>Maintenance</b>	<p>Wash frequently with fresh water to remove salt and dirt.</p> <p><b>Areas worn back to DEKS OLJE® D.1* treated wood:</b></p> <p>Sand with 320 grit paper.</p> <p>Clean worn area with DECK CLEANER* as per label directions. Leave to dry.</p> <p>Top up DEKS OLJE® D.1* as per label directions.</p> <p>Apply required number of DEKS OLJE® D.2 coats to bring up to level of existing finish.</p> <p><b>Rough or Abraded areas:</b></p> <p>Wet sand surface using 320 grit paper and DEKS OLJE® D.1* as the lubricant.</p> <p>Wipe over with a clean, dry, lint free cloth and leave to dry 24 hours.</p> <p>Apply 2 coats of DEKS OLJE® D.2.</p> <p><b>New full coat:</b></p> <p>Wet sand the whole surface using 320 grit paper and DEKS OLJE® D.1* as the lubricant.</p> <p>Wipe over with a clean, dry, lint free cloth and leave to dry 24 hours.</p> <p>Apply 1 or 2 coats of DEKS OLJE® D.2 as desired.</p>
<b>Restrictions</b>	<p>DEKS OLJE® D.2 should only be applied to surfaces treated with DEKS OLJE® D.1* or previously finished with DEKS OLJE® D.2.</p> <p>Do not apply DEKS OLJE® D.2 in wet weather or late in the day when dew or fog may be expected. This may dull a newly set film causing it to blush - exposure to sunlight usually removes the discoloration.</p> <p>DEKS OLJE® D.2 is very slippery, especially when wet and we therefore do not recommend the use of it on decks and other areas where it will be walked on.</p>
<b>Clean-up</b>	<p>Clean all tools and equipment with mineral spirits while still wet. If allowed to dry, remove with paint stripper. Wipe up any drips or runs immediately with a cloth soaked in mineral spirits. Dried DEKS OLJE® D.2 may be removed with MARINE STRIP*.</p> <p>Store and maintain equipment as directed by manufacturer.</p> <p><b>NOTE:</b> Any rags, steel wool etc soaked in DEKS OLJE® D.2 may spontaneously catch fire if improperly discarded. Rags, steel wool etc must be saturated with water after use or placed in a sealed, water filled metal container, before disposing with household waste.</p>
<b>Storage</b>	<ul style="list-style-type: none"> <li>Left over DEKS OLJE® D.2 should be transferred to a smaller, airtight, closed metal or glass container.</li> <li>Keep from freezing and high temperature.</li> </ul>
<b>General information</b>	<p>Every care is taken to ensure that the information provided in this technical data sheet is accurate. <b>OWATROL COATINGS USA</b> is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advise and information please contact our technical department on (954)-929-3905 or email <a href="mailto:info@deksolje.com">info@deksolje.com</a>.</p> <p>The information above is correct at the date of issue.</p>
<b>Safety</b>	<p>Keep out of the reach of children.</p> <p>MSDS available at <a href="http://www.deksolje.com">www.deksolje.com</a>.</p>
<b>Issue date</b>	February 2011.

\* Same manufacturer

