



EXTERIOR



MARINE STRIP

PAINT & ANTIFOULING STRIPPER

Product description	MARINE STRIP is a powerful water washable paint and antifouling stripper that removes varnishes, stains, paints and antifoulings on metal, wood, plastic and gelcoat. Solvent free, MARINE STRIP does not require supervision or immediate removal of the softened paint.
Properties	<ul style="list-style-type: none"> • Solvent free - Non-flammable - No toxic fumes - Is easily removed with water. • MARINE STRIP is safe on all surfaces except Aluminium. • Does not harm plastic. Safe on gelcoat. • Highly efficient - Will remove up to 8 coats of paint in one operation. • Will not affect 2 component or baked-on paints, polyurethane paint and varnishes. • Does not evaporate - Long active work time. • Easy to apply Gel - With prolonged stripping action. • Does not run.
Basic uses	<ul style="list-style-type: none"> • For exterior use only. • Removes varnishes, stains, paints, antifoulings. • Works on metal, wood, plastic, gelcoat. • Horizontal or Vertical surfaces.
Technical data	<p>Viscosity: Thick (concentrate).</p> <p>Specific Gravity: N/A.</p> <p>Physical State: Liquid.</p> <p>Flammability: N/A.</p> <p>Combustibility: N/A.</p> <p>Flash Point: N/A.</p> <p>Shelf Life: 12 months unopened.</p> <p>Container Size: 1L (1.06 U.S. QUART), 2.5L (0.66 U.S. GALLON), 15L (3.96 U.S. GALLON).</p> <p>Appearance & odor: Creamy, caustic soda smell.</p> <p>VOC: N/A.</p>
Application tools	<ul style="list-style-type: none"> • Flat blade or a brush with synthetic (nylon) "bristles". • Powerwasher.

The information set out cons are purely illustrative and are not the responsibility of the manufacturer, the application of products not made under his supervision.

Good application practice

- Always try a sample area first.
- Wear chemical resistant gloves, safety goggles and protective clothing.
- For best results on wood, do not let MARINE STRIP work longer than required to dissolve the paint. "Weak" wood like some veneers or plywoods may be damaged. Hardwood, especially those rich in tannins (oak, exotic wood,...) can turn dark if in prolonged contact with MARINE STRIP.
- Where MARINE STRIP has darkened the wood DO NOT allow it to dry, prior to using DECK CLEANER*.
- Correctly used, MARINE STRIP can easily be removed, then neutralized with DECK CLEANER* which will restore the woods original color.
- Cover areas you want to protect.
- Apply between 41°F (5°C) and 95°F (35°C). Do not apply on a hot surface
- Do not allow MARINE STRIP to dry on the surface. If drying occurs dampen with mist application of water.

Application

- Apply a thick coat of MARINE STRIP over the whole surface to be stripped.
 - Let the product work.
 - To remove MARINE STRIP and dissolved paint, rinse very thoroughly with fresh water and a brush or pressure washer (max. 60 bars/870 psi). The use of hot water makes the job easier.
- NOTE:** Porous surfaces like wood must always be neutralized with DECK CLEANER* after removing MARINE STRIP.

Neutralization

- Always use DECK CLEANER* to neutralize wood surfaces.

Coverage

- 43 ft² (4 m²) per litre.
- Actual coverage will vary depending on type, age and texture of surface.

Clean-up

- Water.

Storage

- DO NOT use metal containers to store product.
- Keep from freezing and away from high temperatures.

General information

Every care is taken to ensure that the information provided in this technical data sheet is accurate. **OWATROL COATINGS USA** is unable to guarantee results as we have no control over the conditions under which our products are applied. For further advise and information please contact our technical department on (954)-929-3905 or email info@deksolje.com.

The information above is correct at the date of issue.

Safety

Keep out of the reach of children.
MSDS available at www.deksolje.com.

Issue date

February 2011.

* Same manufacturer